## 12833 Combustible Gas Leak Detector



Œ

Model 12833 Combustible Gas Leak Detector is ideal for pinpointing small leaks in contaminated environments. Includes soft case, manual & battery.

Detects Natural Gas, Propane, Butane, Methane, Acetone, Alcohol, Ammonia, Steam, Carbon Monoxide, Gasoline, Jet Fuel, Hydrogen Sulfide, Smoke, Industrial Solvents, Lacquer Thinner, Naptha and many more gases.

## Features

16" gooseneck detector for easy measurement in hard to reach areas Pump driven, field calibrateable range

Highly sensitive and reliable

Easy one hand operation

Eliminates background gas concentration with knob adjustable tick rate

Tick accelerates when sensor tip approaches leak

Specifications	
Range	10ppm
Sensor Type	Solid State
Alarm	Visible & Audible @ 10% LEL for Methane
	Can be calibrated for other concentrations or gases
Warm-Up	Approximately 1 minute
Response Time	Less than 2 seconds (up to 40% LEL)
Duty Cycle	Intermittent
Probe Length	16"
Battery	C Alkaline (3 pcs)
Battery Life	8 hours (continuous use)
Size	8.7" x 2.8" x 1.8" (221mm x 72mm x 46mm)
Weight	18oz (520g)